

EX-91017i/ip (17")

Intel 4th Gen. Core i3 panel PC



Features :

- Flat front panel touch screen
- Fanless design
- Intel 4th Gen. Core i3 CPU built-in
- Onboard 4GB DDR 3L 1600 MHz/4GB(option)
- 9~36VDC wide-ranging power input
- IP65 compliant front panel
- Optional projected capacitive touchscreen support 7H anti-scratch surface

Specification:

System	
CPU	Onboard Intel 4 th Gen. Core i3 CPU Processor
System Chipset	SoC
Memory	Onboard 4GB DDR 3L 1600 MHz/8GB(option)
IO Port	
USB	2 x USB 2.0 type A
Serial/Parallel	1 x RS-232 DB-9 1 x DB-9 RS-232/422/485 (Default RS-232)
Audio	1 x Audio Line Out
LAN	2 x GbE LAN RJ-45
HDMI	1 x HDMI Port (Reserved, no Printing)
Power	1 x 3-pin DC Power input terminal 1 x 2-pin power switch
Option	2 x RS-232 DB-9 + 1 x Mini-PCle slot via converter board 2 x CAN bus via converter board 2 x USB 2.0 type A + 1 x Mini-PCle slot + 1xRS-232 DB-9 via converter board 2 x USB 2.0 type A Via converter board

EX-91017i/ip (17")

Intel 4th Gen. Core i3 panel PC

Storage Space	
HDD	1 x 2.5" SATA HDD bay for SATA HDD
Movable device	1 x SD card slot, up to 32GB
Expansion Bus	1 x Internal Mini-PCle slot full size
Display	
LCD Size	17"
Max. Resolution	1280 x 1024
Max. Color	16.7M
Luminance (cd/m ²)	350
Contrast Ratio	1000:1
Viewing Angle	170(H)/160(V)
Backlight Lifetime	30,000 hrs
Touch screen - Resistive Touch Window Type	
Interface	USB
Light Transmission	Over 80%
Touch Screen - Projected Capacitive Type	
Interface	USB
Light Transmission	Over 90%
Power	
Power input	9~36V/DC
Power Consumption	39.6W
Mechanical	
Front Bezel Metal	Aluminum / Panel Mounting
Rear Panel Metal	Aluminum / VESA Mount 100 x 100
IP Rating	Front Panel IP65
Dimension (mm)	439 x 348 x 64.8 mm
Net Weight	5.1Kg
Environmental	
Operating temperature(°C)	0~50°C
Storage temperature(°C)	-20~60°C
Storage humidity	10 to 90% @ 40°C, non- condensing
Certification	Meet CE / FCC CLASS A
Operating System Support	Windows 7 64-bit, WES 7, WES 8, Windows 8.1

EX-91017i/ip (17")

Intel 4th Gen. Core i3 panel PC

Dimension :

